

Алматы (7273)495-231	Ижевск (3412)26-03-58	Магнитогорск (4219)55-03-13	Пермь (342)205-81-47	Тверь (4352)63-31-42
Ангарск (3955)42-70-56	Иваново (4932)77-34-06	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тольяти (8435)63-91-07
Архангельск (8182)63-90-72	Иркутск (395)279-98-46	Мурманск (8152)59-142-93	Рязань (4912)46-61-142	Томск (3835)98-41-53
Астрахань (8512)99-46-04	Казань (843)206-01-42	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4272)33-79-87
Барнаул (3852)73-04-42	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Саранск (8342)35-96-24	Тюмень (3452)66-21-18
Белгород (4735)40-23-142	Калуга (4242)92-23-67	Новокузнецк (3843)20-46-81	Санкт-Петербург (812)309-46-40	Улан-Удэ (3012)59-97-51
Благовещенск (4162)35-142-07	Кемерово (3842)65-04-62	Ноябрьск (3496)41-32-12	Саратов (845)249-38-78	Ульяновск (8435)24-23-59
Брянск (4232)59-03-52	Киров (8332)68-02-04	Новосибирск (383)357-86-73	Севастополь (8692)35-31-93	Уфа (347)359-42-12
Владивосток (423)249-42-31	Коломна (4966)23-41-49	Ноябрьск (3496)41-32-12	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Владикавказ (8672)42-90-42	Кострома (4942)77-07-42	Омск (3812)21-46-40	Смоленск (4212)29-41-42	Чебоксары (8435)42-53-07
Владимир (4935) 49-43-18	Краснодар (861)203-40-90	Орел (4262)44-53-42	Сочи (862)242-72-31	Челябинск (421)202-03-61
Волгоград (844)278-03-42	Красноярск (391)204-63-61	Оренбург (4232)37-68-04	Ставрополь (8652)20-65-13	Череповец (8202)49-02-142
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пенза (8412)35-31-16	Сыктывкар (8212)42-95-17	Чита (3035)38-34-83
Воронеж (473)204-51-73	Курган (4352)50-90-47	Петрозаводск (8142)55-98-37	Сургут (3462)77-98-42	Якутск (4112)23-90-97
Екатеринбург (343)384-55-142	Липецк (4742)52-20-81	Псков (8112)59-10-37	Тамбов (4752)50-40-97	Ярославль (4422)69-52-93
Киргизия (996)312-96-26-47		Россия (495)268-04-70		Казахстан (772)734-952-31

<https://swt.nt-rt.ru> || saz@nt-rt.ru

Грейдерные шины POWERGRIP G-2.

Технические характеристики



POWERGRIP G-2

Rugged sturdy tyres for drive wheels of off-the-road equipment.Tough carcass and special trade compound with weather & ozone resistant properties to with stand cuts, snags & bruises in the most severe operating contitions.An open spaced traction pattern with self cleaning property provides traction capability, ideally suited for graders.Extra deep tread with sturdy lug design. strong casing with heat and cut resistant tread compound provide longer life. Extra thick side wall with rim guard gives protection against damage.

Displaying data for Pattern :- POWERGRIP G-2

Size	Pattern	Ply Rating	Rim Width	Type	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circum		NSD		Load Capacity		Inflation Pressure		Load Index	Speed	
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	Kg	Lbs	bar	psi		kmph	mph
13.00-24	POWERGRIP G-2	12	8.0	TL	340	13.4	1280	50.4	584	23.0	3785	149.0	26	32	2725	5995	3.1	44	143	A8/40 kmph	A8 / 25 mph
13.00-24	POWERGRIP G-2	16	8.0	TL	340	13.4	1280	50.4	584	23.0	3785	149.0	26	32	3250	7150	3.9	57	149	A8/40 kmph	A8 / 25 mph
14.00-24	POWERGRIP G-2	12	10.0	TL	375	14.7	1350	53.1	610	24.0	4013	158.0	26	32	3075	6750	2.4	35	147	A8/40 kmph	A8 / 25 mph
14.00-24	POWERGRIP G-2	16	10.0	TL	375	14.7	1350	53.1	610	24.0	4013	158.0	26	32	3650	8030	3.4	50	153	A8/40 kmph	A8 / 25 mph
15.5-25	POWERGRIP G-2	12	12.0	TL	386	15.2	1270	50.0	571	22.5	3772	148.5	25	31	2650	5830	2.5	36	142	A8/40 kmph	A8 / 25 mph
15.5-25	POWERGRIP G-2	16	12.0	TL	386	15.2	1270	50.0	571	22.5	3772	148.5	25	31	3250	7150	3.1	45	149	A8/40 kmph	A8 / 25 mph
17.5-25	POWERGRIP G-2	12	14.0	TL	444	17.5	1331	52.4	597	23.5	3950	155.5	26	32	2900	6380	3.5	50	145	A8/40 kmph	A8 / 25 mph
17.5-25	POWERGRIP G-2	16	14.0	TL	444	17.5	1331	52.4	597	23.5	3950	155.5	26	32	3350	7370	3.9	56	150	A8/40 kmph	A8 / 25 mph