

Алматы (7273)495-231
Ангарск (3955)42-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-42
Белгород (4735)40-23-142
Благовещенск (4162)35-142-07
Брянск (4232)59-03-52
Владивосток (423)249-42-31
Владикавказ (8672)42-90-42
Владимир (4935) 49-43-18
Волгоград (844)278-03-42
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-142

Ижевск (3412)26-03-58
Иваново (4932)77-34-06
Иркутск (395)279-98-46
Казань (843)206-01-42
Калининград (4012)72-03-81
Калуга (4242)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-42
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (4352)50-90-47
Липецк (4742)52-20-81

Магнитогорск (4219)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-142-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)357-86-73
Ноябрьск (3496)41-32-12
Омск (3812)21-46-40
Орел (4262)44-53-42
Оренбург (4232)37-68-04
Пенза (8412)35-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-142
Самара (846)206-03-16
Саранск (8342)35-96-24
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)35-31-93
Симферополь (3652)67-13-56
Смоленск (4212)29-41-42
Сочи (862)242-72-31
Ставрополь (8652)20-65-13
Сыктывкар (8212)42-95-17
Сургут (3462)77-98-42
Тамбов (4752)50-40-97

Тверь (4352)63-31-42
Тольятти (8435)63-91-07
Томск (3835)98-41-53
Тула (4272)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Ульяновск (8435)24-23-59
Уфа (347)359-42-12
Хабаровск (4212)92-98-04
Чебоксары (8435)42-53-07
Челябинск (421)202-03-61
Череповец (8202)49-02-142
Чита (3035)38-34-83
Якутск (4112)23-90-97
Ярославль (4422)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://swt.nt-rt.ru> || saz@nt-rt.ru

Радиальные тракторные шины со стальным
ремнем (R-1W) SR-666/777/888.
Технические характеристики

SR-666

Radial tyre with balanced characteristics for wide range of applications both on the field and on the road.

Larger ground contact patch makes the tyre well suited for handling grassland.

Long service life thanks to the use of a wear resistant tread compound.

Deeper Tread providing longer tyre life.

Prominent Rim Guard, protecting rim flange from damage.

Displaying data for Pattern :- SR-666

Size	Pattern	Rim Width		Type	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circum		NSD		Load Capacity				Inflation Pressure		Load Index	Speed			
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	40kmph / 25 mph		65kmph / 40 mph		bar	psi		kmph	mph		
															MAX LOAD	MAX LOAD	MAX LOAD	MAX LOAD							
															Kg	Lbs	Kg	Lbs							
440/65R-24 135 D/138 A8	SR-666	W 14L	W 13 W 15L	TL	442	17.4	1181	46.5	538	21.2	3546	139.6	47	59	2360	5195	2180	4800	2.4	35	135	D/65kmph	D/40 mph		
540/65R-24 146 D/149 A8	SR-666	W 16L	W 18L	TL	531	20.9	1313	51.7	589	23.2	3929	154.7	50	63	3250	7150	3000	6600	2.4	35	146	D/65kmph	D/40 mph		
440/65R-28 138 D/141 A8	SR-666	W 14L	W 13 W 15L	TL	442	17.4	1283	50.5	589	23.2	3879	152.7	47	59	2575	5665	2360	5195	2.4	35	138	D/65kmph	D/40 mph		
480/65R-28 142 D/145 A8	SR-666	W 15L	W 14L	TL	480	18.9	1335	52.6	610	24.0	4059	159.8	48	60	2900	6380	2650	5830	2.4	35	142	D/65kmph	D/40 mph		
540/65R-28 149 D/152 A8	SR-666	W 16L	W 18L	TL	540	21.2	1413	55.6	643	25.3	4253	167.5	50	62	3550	7810	3250	7150	2.4	35	149	D/65kmph	D/40 mph		
540/65R-38 153 D/156 A8	SR-666	W 16L	W 18L	TL	531	20.9	1667	65.6	760	29.9	5059	199.2	51	63	4010	8820	3660	8050	2.4	35	153	D/65kmph	D/40 mph		
600/65R-38 159 D/162 A8	SR-666	DW 20B	W 18L	TL	600	23.6	1745	68.7	790	31.1	5248	206.6	56	70	4750	10450	4375	9625	2.4	35	159	D/65kmph	D/40 mph		
650/65R-38 163 D/166 A8	SR-666	DW 20B	W 9	TL	643	25.3	1808	71.2	830	32.7	5479	215.7	60	75	5600	12320	4875	10725	2.4	35	163	D/65kmph	D/40 mph		



SR-777

Radial tyre with balanced characteristics for wide range of applications both on the field and on the road.

Larger ground contact patch makes the tyre well suited for handling grassland.

Long service life thanks to the use of a wear resistant tread compound.

Deeper Tread providing longer tyre life.

Prominent Rim Guard, protecting rim flange from damage.

Displaying data for Pattern :- SR-777

Size	Pattern	Rim Width		Type	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circum		NSD		Load Capacity				Inflation Pressure		Load Index	Speed	
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	40kmph / 25 mph		65kmph / 40 mph		bar	psi		kmph	mph
															MAX LOAD		MAX LOAD						
															Kg	Lbs	Kg	Lbs					
200/70R-16 94 A8/B	SR-777	W 6	-	TL	198	7.8	686	27.0	312	12.3	2057	81.0	28	35	670	1475	670	1475	2.4	35	94	B/50 kmph	B/30 mph
240/70R-16 104 A8/B	SR-777	W8	W8L W9L	TL	241	9.5	742	29.2	335	13.2	2225	87.6	31	38	900	1980	900	1980	2.4	35	104	B/50 kmph	B/30 mph
260/70R-16 109 A8/B	SR-777	W8	W8L W9L	TL	259	10.2	770	30.3	345	13.6	2309	90.9	32	39	1030	2265	1030	2265	2.4	35	109	B/50 kmph	B/30 mph
280/70R-16 112 A8/B	SR-777	W9	W8 W8L W 10	TL	282	11.1	798	31.4	356	14.0	2370	93.3	33	41	1120	2465	1120	2465	2.4	35	112	B/50 kmph	B/30 mph
280/70R-18 114 A8/B	SR-777	W 9	W8 W 10	TL	282	11.1	849	33.4	381	15.0	2547	100.3	33	41	1180	2595	1180	2595	2.4	35	114	B/50 kmph	B/30 mph
300/70R-20 120 A8/B	SR-777	W9	W 10	TL	295	11.6	952	37.5	428	16.8	2854	112.4	33	41	1400	3080	1400	3080	2.4	35	120	B/50 kmph	B/30 mph
320/70R-20 123 A8/B	SR-777	DW 20B	W 9 W 11	TL	320	12.6	983	38.7	444	17.5	2964	116.7	34	43	1550	3410	1550	3410	2.4	35	123	B/50 kmph	B/30 mph
360/70R-20 129 A8/B	SR-777	W 11	W 10 W 12	TL	358	14.1	1041	41.0	470	18.5	3122	122.9	42	53	1850	4070	1850	4070	1.6	23	129	B/50 kmph	B/30 mph
320/70R-24 116A8/B	SR-777	W 10	W9 W 11	TL	320	12.6	1095	43.1	503	19.8	3240	127.8	41	51	1250	2750	1250	2750	1.6	23	116	B/50 kmph	B/30 mph
360/70R-24 122 A8/B	SR-777	W 11	W 10 W11	TL	358	14.1	1153	45.4	518	20.4	3454	136.0	42	53	1500	3300	1500	3300	1.6	23	122	B/50 kmph	B/30 mph
380/70R-24 125 A8/B	SR-777	W 12	W 11 W 13	TL	381	15.0	1191	46.9	538	21.2	3561	140.2	43	54	1650	3630	1650	3630	1.6	23	125	B/50 kmph	B/30 mph
420/70R-24 130 A8/B	SR-777	W 13	W 12 W14L	TL	419	16.5	1222	48.1	579	22.8	3561	144.9	45	56	1900	4180	1900	4180	1.6	23	130	B/50 kmph	B/30 mph
380/70R-28 127 A8/B	SR-777	W 12	W11 W 13	TL	381	15.0	1293	50.9	587	23.1	3884	152.9	43	54	1750	3850	1750	3850	1.6	23	127	B/50 kmph	B/30 mph
420/70R-28 133 A8/B	SR-777	W 13	W 12 W 14	TL	419	16.5	1349	53.1	610	24.0	3988	157.0	47	59	2060	4540	2060	4535	1.6	23	133	B/50 kmph	B/30 mph
600/70R-30 152 A8/B	SR-777	DW 206	DW 18L W 18L	TL	592	23.3	1603	63.1	711	28.0	4775	188.0	59	74	3550	7810	3550	7810	1.6	23	152	B/50 kmph	B/30 mph
400/75R-38 15.5R-38 140 A8/B	SR-777	W 14	W14	TL	394	15.5	1570	62.0	730	29.0	4685	184.0	47	59	2500	5500	2500	5500	1.6	23	140	B/50 kmph	B/30 mph
710/70R-38 178 A8/B	SR-777	DW 23B		TL	716	28.2	1958	77.1	859	33.8	5751	226.4	52	65	7500	16500	7500	16500	2.9	42	178	B/50 kmph	B/30 mph
710/70R-42 173 A8/B	SR-777	DW 23B		TL	716	28.2	2060	81.1	922	36.3	6175	243.1	60	75	6500	14300	6500	14300	2.4	35	173	B/50 kmph	B/30 mph



SR-888

Radial tyre with balanced characteristics for wide range of applications both on the field and on the road.

Larger ground contact patch makes the tyre well suited for handling grassland.

Long service life thanks to the use of a wear resistant tread compound.

Deeper Tread providing longer tyre life.

Prominent Rim Guard, protecting rim flange from damage.

Displaying data for Pattern :- SR-888

Size	Pattern	Rim Width		Type	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circum		NSD		Load Capacity				Inflation Pressure		Load Index	Speed	
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	40kmph / 25 mph MAX LOAD		65kmph / 40 mph MAX LOAD		bar	psi		kmph	mph
														Kg	Lbs	Kg	Lbs						
250 / 85R - 20 9.5R - 20 116 A8 / B	SR-888	W 8	W7 W 9	TL	249	9.8	940	37.0	424	16.7	2812	110.7	38	48	1250	2750	1250	2750	2.4	35	116	B / 50 kmph	B / 30 mph
280 / 85R - 20 11.2R - 20 112 A8 / B	SR-888	W 10	W9	TL	292	11.5	983	38.7	442	17.4	2951	116.2	39	49	1120	2464	1120	2464	1.6	23	112	B / 50 kmph	B / 30 mph
250 / 85R - 24 9.5R - 24 109 A8 / B	SR-888	W8	W 7 W9	TL	251	9.9	1036	40.8	475	18.7	3104	122.2	42	53	1030	2465	1030	2465	1.6	23	109	B / 50 kmph	B / 30 mph
280 / 85R - 24 11.2R - 24 115 A8 / B	SR-888	W 10	W9	TL	292	11.5	1087	42.8	508	20.0	3226	127.0	41	51	1215	2675	1215	2675	1.6	23	115	B / 50 kmph	B / 30 mph
320 / 85R - 24 12.4R - 24 122 A8 / B	SR-888	W 11	W 9 W 10	TL	330	13.0	1153	45.4	518	20.4	3424	134.8	43	54	1500	3300	1500	3300	1.6	23	122	B / 50 kmph	B / 30 mph
340 / 85R - 24 13.6R - 24 125 A8 / B	SR-888	W 12	W 11	TL	343	13.5	1188	46.8	533	21.0	3531	139.0	44	55	1650	3630	1650	3630	1.6	23	125	B / 50 kmph	B / 30 mph
380 / 85R - 24 14.9R - 24 131 A8 / B	SR-888	W 12	W 11 W 13	TL	381	15.0	1255	49.4	559	22.0	3706	145.9	45	56	1950	4290	1950	4290	1.6	23	131	B / 50 kmph	B / 30 mph
250 / 85R - 28 9.5R - 28 112 A8 / B	SR-888	W 8	W 7 W9	TL	251	9.9	1138	44.8	518	20.4	3321	134.7	38	48	1120	2465	1120	2465	1.6	23	112	B / 50 kmph	B / 30 mph
280 / 85R - 28 11.2R - 28 118 A8 / B	SR-888	W 10	W 9	TL	292	11.5	1186	46.7	546	21.5	3559	140.1	42	53	1320	2904	1320	2904	1.6	23	118	B / 50 kmph	B / 30 mph
320 / 85R - 28 12.4R - 28 124 A8 / B	SR-888	W 11	W 9 W 10	TL	320	12.6	1255	49.4	559	22.0	3734	147.0	42	53	1600	3520	1600	3520	1.6	23	124	B / 50 kmph	B / 30 mph
340 / 85R - 28 13.6R - 28 127 A8 / B	SR-888	W 12	W 11	TL	353	13.9	1288	50.7	584	23.0	3835	151.0	42	53	1750	3850	1750	3850	1.6	23	127	B / 50 kmph	B / 30 mph
380 / 85R - 28 14.9R - 28 133 A8 / B	SR-888	W 12	W 11 W 13	TL	381	15.0	1356	53.4	607	23.9	4016	158.1	45	56	2060	4535	2060	4535	1.6	23	133	B / 50 kmph	B / 30 mph

Size	Pattern	Rim Width		Type	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circum		NSD		Load Capacity				Inflation Pressure		Load Index	Speed	
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	40kmph / 25 mph MAX LOAD		65kmph / 40 mph MAX LOAD		bar	psi		kmph	mph
420 / 85R - 28 16.9R - 28 139 A8 / B	SR-888	W 15	W 13 W 14	TL	419	16.5	1425	56.1	635	25.0	4242	167.0	49	61	2430	5345	2430	5345	1.6	23	139	B / 50 kmph	B / 30 mph
380 / 85R - 30 14.9R - 30 135 A8 / B	SR-888	W 12	W 11 W 13	TL	381	15.0	1407	55.4	630	24.8	4153	163.5	45	56	2180	4796	2180	4796	1.6	23	135	B / 50 kmph	B / 30 mph
420 / 85R - 30 16.9R - 30 140 A8 / B	SR-888	W 15	W 13 W 14	TL	419	16.5	1476	58.1	660	26.0	4394	173.0	45	56	2500	5500	2500	5500	1.6	23	140	B / 50 kmph	B / 30 mph
460 / 85R - 30 18.4R - 30 145 A8 / B	SR-888	W 16 L	W 14 L W 15 L	TL	475	18.7	1544	60.8	683	26.9	4536	178.6	54	67	2900	6380	2900	6380	1.6	23	145	B / 50 kmph	B / 30 mph
380 / 85R - 34 14.9R - 34 137 A8 / B	SR-888	W 12	W 11 W 13	TL	381	15.0	1514	59.6	686	27.0	4470	176.0	45	56	2300	5060	2300	5060	1.6	23	137	B / 50 kmph	B / 30 mph
420 / 85R - 34 16.9R - 34 142 A8 / B	SR-888	W 15	W 13 W 14	TL	419	16.5	1577	62.1	711	28.0	4674	184.0	49	61	2650	5830	2650	5830	1.6	23	142	B / 50 kmph	B / 30 mph
460 / 85R - 34 18.4R - 34 147 A8 / B	SR-888	W 16	W 14 W 15	TL	475	18.7	1646	64.8	737	29.0	4851	191.0	50	63	3075	6765	3075	6765	1.6	23	147	B / 50 kmph	B / 30 mph
340 / 85R - 38 13.6R - 38 133 A8 / B	SR-888	W 12	W 11	TL	353	13.9	1543	60.7	712	28.0	4668	183.8	52	65	2060	4532	2060	4532	1.6	23	133	B / 50 Kmph	B / 30 mph
420 / 85R - 38 16.9R - 38 144 A8 / B	SR-888	W 15	W 13 W 14	TL	419	16.5	1679	66.1	762	30.0	5004	197.0	52	65	2800	6160	2800	6160	1.6	23	144	B / 50 Kmph	B / 30 mph
460 / 85R - 38 18.4R - 38 149 A8 / B	SR-888	W 16	W 14 W 15	TL	455	17.9	1748	68.8	787	31.0	5156	203.0	55	69	3250	7150	3250	7150	1.6	23	149	B / 50 Kmph	B / 30 mph
520 / 85R - 38 20.8R - 38 155 A8 / B	SR-888	DW 18	DW 16L DW 18L	TL	516	20.3	1849	72.8	813	32.0	5410	213.0	59	74	3875	8525	3875	8525	1.6	23	155	B / 50 Kmph	B / 30 mph
480 / 80R - 42 18.4R - 42 151 A8 / B	SR-888	W 16	DW 16	TL	480	18.9	1836	72.3	838	33.0	5461	215.0	54	68	3450	7590	3450	7590	1.6	23	151	B / 50 Kmph	B / 30 mph
520 / 85R - 42 20.8R - 42 157 A8 / B	SR-888	DW 18L	DW 16	TL	516	20.3	1951	76.8	859	33.8	5735	225.8	58	73	4125	9075	4125	9075	1.6	23	157	B / 50 Kmph	B / 30 mph
480 / 80R - 46 18.4R - 46 158 A8 / B	SR-888	W 16	DW 16	TL	480	18.9	1933	76.1	889	35.0	5791	228.0	52	65	4250	9350	4250	9350	2.4	35	158	B / 50 Kmph	B / 30 mph
340 / 85R - 48 13.6R - 48 152 A8 / B	SR-888	W 12	W 11	TL	353	13.9	1798	70.8	838	33.0	5385	212.0	44	55	3550	7810	3550	7810	4.1	58	152	B / 50 Kmph	B / 30 mph

Алматы (7273)495-231
Ангарск (3955)42-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-42
Белгород (4735)40-23-142
Благовещенск (4162)35-142-07
Брянск (4232)59-03-52
Владивосток (423)249-42-31
Владикавказ (8672)42-90-42
Владимир (4935) 49-43-18
Волгоград (844)278-03-42
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-142

Ижевск (3412)26-03-58
Иваново (4932)77-34-06
Иркутск (395)279-98-46
Казань (843)206-01-42
Калининград (4012)72-03-81
Калуга (4242)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-42
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (4352)50-90-47
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (4219)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-142-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Ноябрьск (3496)41-32-12
Новосибирск (383)357-86-73
Ноябрьск (3496)41-32-12
Омск (3812)21-46-40
Орел (4262)44-53-42
Оренбург (4232)37-68-04
Пенза (8412)35-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37

Россия (495)268-04-70

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-142
Самара (846)206-03-16
Саранск (8342)35-96-24
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)35-31-93
Симферополь (3652)67-13-56
Смоленск (4212)29-41-42
Сочи (862)242-72-31
Ставрополь (8652)20-65-13
Сыктывкар (8212)42-95-17
Сургут (3462)77-98-42
Тамбов (4752)50-40-97

Казахстан (772)734-952-31

Тверь (4352)63-31-42
Тольяти (8435)63-91-07
Томск (3835)98-41-53
Тула (4272)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Ульяновск (8435)24-23-59
Уфа (347)359-42-12
Хабаровск (4212)92-98-04
Чебоксары (8435)42-53-07
Челябинск (421)202-03-61
Череповец (8202)49-02-142
Чита (3035)38-34-83
Якутск (4112)23-90-97
Ярославль (4422)69-52-93