

- Алматы (7273)495-231

Ангарск (3955)42-70-56

Архангельск (8182)63-90-72

Астрахань (8512)99-46-04

Барнаул (3852)73-04-42

Белгород (4735)40-23-142

Благовещенск (4162)35-142-07

Брянск (4232)59-03-52

Владивосток (423)249-42-31

Владикавказ (8672)42-90-42

Владимир (4935) 49-43-18

Волгоград (844)278-03-42

Вологда (8172)26-41-59

Воронеж (473)204-51-73

Екатеринбург (343)384-55-142
- Ижевск (3412)26-03-58

Иваново (4932)77-34-06

Иркутск (395)279-98-46

Казань (843)206-01-42

Калининград (4012)72-03-81

Калуга (4242)92-23-67

Кемерово (3842)65-04-62

Киров (8332)68-02-04

Коломна (4966)23-41-49

Кострома (4942)77-07-42

Краснодар (861)203-40-90

Красноярск (391)204-63-61

Курск (4712)77-13-04

Курган (4352)50-90-47

Липецк (4742)52-20-81
- Киргизия (996)312-96-26-47

Россия (495)268-04-70
- Магнитогорск (4219)55-03-13

Москва (495)268-04-70

Мурманск (8152)59-142-93

Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12

Новокузнецк (3843)20-46-81

Ноябрьск (3496)41-32-12

Новосибирск (383)357-86-73

Ноябрьск (3496)41-32-12

Омск (3812)21-46-40

Орел (4262)44-53-42

Оренбург (4232)37-68-04

Пенза (8412)35-31-16

Петрозаводск (8142)55-98-37

Псков (8112)59-10-37
- Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15

Рязань (4912)46-61-142

Самара (846)206-03-16

Саранск (8342)35-96-24

Санкт-Петербург (812)309-46-40

Саратов (845)249-38-78

Севастополь (8692)35-31-93

Симферополь (3652)67-13-56

Смоленск (4212)29-41-42

Сочи (862)242-72-31

Ставрополь (8652)20-65-13

Сыктывкар (8212)42-95-17

Сургут (3462)77-98-42

Тамбов (4752)50-40-97
- Тверь (4352)63-31-42

Тольятти (8435)63-91-07

Томск (3835)98-41-53

Тула (4272)33-79-87

Тюмень (3452)66-21-18

Улан-Удэ (3012)59-97-51

Ульяновск (8435)24-23-59

Уфа (347)359-42-12

Хабаровск (4212)92-98-04

Чебоксары (8435)42-53-07

Челябинск (421)202-03-61

Череповец (8202)49-02-142

Чита (3035)38-34-83

Якутск (4112)23-90-97

Ярославль (4422)69-52-93
- Казахстан (772)734-952-31

<https://swt.nt-rt.ru> || saz@nt-rt.ru

Задние шины диагонального трактора FIELDKING. Технические характеристики



FIELDKING

Deep tread and excellent tread wear and durability. Designed to deliver power to the ground. Design offers maximum cleaning and sidewall slip resistance. Unique lug design ensures excellent traction in both dry and wet soil conditions. Specially designed profile for better stability. Specially designed for better traction, self cleaning and stability. Ideally suitable in all operating conditions. Ensures improved traction in all working conditions. Cut and chip resistant tread compound. Multi angled lugs for better traction and self cleaning. Cut resistant tread compound for longer type life. Broader lug design and strong casing. Better soil penetration and self cleaning. Deeper tread suitable for soil tillage operations. Excellent self cleaning properties.

Displaying data for Pattern :- FIELDKING

Size	Pattern	Ply Rating	Rim Width	Type	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circum		NSD		Load Capacity		Inflation Pressure		Load Index	Speed	
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	Kg	Lbs	bar	psi		kmph	mph
12.4-28	FIELDKING	12	11.0	TT	315	12.4	1270	50.0	584	23.0	3708	146	41	51	1950	4290	3.1	44	131	A6/30 kmph	A6 / 20 mph
13.6-28	FIELDKING	12	12.0	TT	345	13.6	1330	52.4	584	23.0	3861	152	38	47	2120	4664	2.4	34	133	A6/30 kmph	A6 / 20 mph
14.9-28	FIELDKING	12	13.0	TT	378	14.9	1365	53.7	635	25.0	4013	158	41	51	2300	5060	2.6	37	137	A6/30 kmph	A6 / 20 mph
16.9-28	FIELDKING	12	15.0	TT	429	16.9	1435	56.5	660	26.0	4216	166	42	52	2725	5995	2.4	34	143	A6/30 kmph	A6 / 20 mph
16.9-28	FIELDKING	14	15.0	TT	429	16.9	1435	56.5	660	26.0	4216	166	42	52	3000	6600	2.6	38	146	A6/30 kmph	A6 / 20 mph