

Алматы (7273)495-231	Ижевск (3412)26-03-58	Магнитогорск (4219)55-03-13	Пермь (342)205-81-47	Тверь (4352)63-31-42
Ангарск (3955)42-70-56	Иваново (4932)77-34-06	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тольятти (8435)63-91-07
Архангельск (8182)63-90-72	Иркутск (395)279-98-46	Мурманск (8152)59-142-93	Рязань (4912)46-61-142	Томск (3835)98-41-53
Астрахань (8512)99-46-04	Казань (843)206-01-42	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4272)33-79-87
Барнаул (3852)73-04-42	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Саранск (8342)35-96-24	Тюмень (3452)66-21-18
Белгород (4735)40-23-142	Калуга (4242)92-23-67	Новокузнецк (3843)20-46-81	Санкт-Петербург (812)309-46-40	Улан-Удэ (3012)59-97-51
Благовещенск (4162)35-142-07	Кемерово (3842)65-04-62	Ноябрьск (3496)41-32-12	Саратов (845)249-38-78	Ульяновск (8435)24-23-59
Брянск (4232)59-03-52	Киров (8332)68-02-04	Новосибирск (383)357-86-73	Севастополь (8692)35-31-93	Уфа (347)359-42-12
Владивосток (423)249-42-31	Коломна (4966)23-41-49	Ноябрьск (3496)41-32-12	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Владикавказ (8672)42-90-42	Кострома (4942)77-07-42	Омск (3812)21-46-40	Смоленск (4212)29-41-42	Чебоксары (8435)42-53-07
Владимир (4935) 49-43-18	Краснодар (861)203-40-90	Орел (4262)44-53-42	Сочи (862)242-72-31	Челябинск (421)202-03-61
Волгоград (844)278-03-42	Красноярск (391)204-63-61	Оренбург (4232)37-68-04	Ставрополь (8652)20-65-13	Череповец (8202)49-02-142
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пенза (8412)35-31-16	Сыктывкар (8212)42-95-17	Чита (3035)38-34-83
Воронеж (473)204-51-73	Курган (4352)50-90-47	Петрозаводск (8142)55-98-37	Сургут (3462)77-98-42	Якутск (4112)23-90-97
Екатеринбург (343)384-55-142	Липецк (4742)52-20-81	Псков (8112)59-10-37	Тамбов (4752)50-40-97	Ярославль (4422)69-52-93
Киргизия (996)312-96-26-47		Россия (495)268-04-70	Казахстан (772)734-952-31	

<https://swt.nt-rt.ru>
||
saz@nt-rt.ru

Задние шины диагонального трактора POWERLUG. Технические характеристики



POWERLUG

Deep tread and excellent tread wear and durability. Designed to deliver power to the ground. Design offers maximum cleaning and sidewall slip resistance. Unique lug design ensures excellent traction in both dry and wet soil conditions. Specially designed profile for better stability. Specially designed for better traction, self cleaning and stability. Ideally suitable in all operating conditions. Ensures improved traction in all working conditions. Cut and chip resistant tread compound. Multi angled lugs for better traction and self cleaning. Cut resistant tread compound for longer type life. Broader lug design and strong casing. Better soil penetration and self cleaning. Deeper tread suitable for soil tillage operations. Excellent self cleaning properties.

Displaying data for Pattern :- POWERLUG

Size	Pattern	Ply Rating	Rim Width	Type	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circum		NSD		Load Capacity		Inflation Pressure		Load Index	Speed	
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	Kg	Lbs	bar	psi		kmph	mph
12.4-28	POWERLUG	12	11.0	TT	315	12.4	1270	50.0	584	23.0	3708	146.0	39	49	1950	4290	3.1	44	131	A6/30 kmph	A6 / 20 mph
13.6-28	POWERLUG	12	12.0	TT	345	13.6	1330	52.4	584	23.0	3861	152.0	40	50	2120	4664	2.4	34	133	A6/30 kmph	A6 / 20 mph
18.4-30	POWERLUG	8	16.0	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	42	52	2430	5345	1.6	23	139	A6/30 kmph	A6 / 20 mph
18.4-30	POWERLUG	10	16.0	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	42	52	2900	6380	1.8	26	145	A6/30 kmph	A6 / 20 mph
18.4-30	POWERLUG	14	16.0	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	42	52	3450	7590	2.6	38	151	A6/30 kmph	A6 / 20 mph