

- Алматы (7273)495-231

Ангарск (3955)42-70-56

Архангельск (8182)63-90-72

Астрахань (8512)99-46-04

Барнаул (3852)73-04-42

Белгород (4735)40-23-142

Благовещенск (4162)35-142-07

Брянск (4232)59-03-52

Владивосток (423)249-42-31

Владикавказ (8672)42-90-42

Владимир (4935) 49-43-18

Волгоград (844)278-03-42

Вологда (8172)26-41-59

Воронеж (473)204-51-73

Екатеринбург (343)384-55-142
- Ижевск (3412)26-03-58

Иваново (4932)77-34-06

Иркутск (395)279-98-46

Казань (843)206-01-42

Калининград (4012)72-03-81

Калуга (4242)92-23-67

Кемерово (3842)65-04-62

Киров (8332)68-02-04

Коломна (4966)23-41-49

Кострома (4942)77-07-42

Краснодар (861)203-40-90

Красноярск (391)204-63-61

Курск (4712)77-13-04

Курган (4352)50-90-47

Липецк (4742)52-20-81
- Магнитогорск (4219)55-03-13

Москва (495)268-04-70

Мурманск (8152)59-142-93

Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12

Новокузнецк (3843)20-46-81

Ноябрьск (3496)41-32-12

Новосибирск (383)357-86-73

Ноябрьск (3496)41-32-12

Омск (3812)21-46-40

Орел (4262)44-53-42

Оренбург (4232)37-68-04

Пенза (8412)35-31-16

Петрозаводск (8142)55-98-37

Псков (8112)59-10-37
- Пермь (342)205-81-47

Ростов-на-Дону (863)308-18-15

Рязань (4912)46-61-142

Самара (846)206-03-16

Саранск (8342)35-96-24

Санкт-Петербург (812)309-46-40

Саратов (845)249-38-78

Севастополь (8692)35-31-93

Симферополь (3652)67-13-56

Смоленск (4212)29-41-42

Сочи (862)242-72-31

Ставрополь (8652)20-65-13

Сыктывкар (8212)42-95-17

Сургут (3462)77-98-42

Тамбов (4752)50-40-97
- Тверь (4352)63-31-42

Тольяти (8435)63-91-07

Томск (3835)98-41-53

Тула (4272)33-79-87

Тюмень (3452)66-21-18

Улан-Удэ (3012)59-97-51

Ульяновск (8435)24-23-59

Уфа (347)359-42-12

Хабаровск (4212)92-98-04

Чебоксары (8435)42-53-07

Челябинск (8421)202-03-61

Череповец (8202)49-02-142

Чита (3035)38-34-83

Якутск (4112)23-90-97

Ярославль (4422)69-52-93
- Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://swt.nt-rt.ru> || saz@nt-rt.ru

Задние шины диагонального трактора TR-21. Технические характеристики



TR-21

Deep tread and excellent tread wear and durability. Designed to deliver power to the ground. Design offers maximum cleaning and sidewall slip resistance. Unique lug design ensures excellent traction in both dry and wet soil conditions. Specially designed profile for better stability. Specially designed for better traction, self cleaning and stability. Ideally suitable in all operating conditions. Ensures improved traction in all working conditions. Cut and chip resistant tread compound. Multi angled lugs for better traction and self cleaning. Cut resistant tread compound for longer type life. Broader lug design and strong casing. Better soil penetration and self cleaning. Deeper tread suitable for soil tillage operations. Excellent self cleaning properties.

Displaying data for Pattern :- TR-21

Size	Pattern	Ply Rating	Rim Width	Type	Section Width		Overall Diameter		Static Loaded Radius		Rolling Circum		NSD		Load Capacity		Inflation Pressure		Load Index	Speed	
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	Kg	Lbs	bar	psi		kmph	mph
16.9-30	TR-21	8	15	TT	429	16.9	1486	58.5	686	27	4369	172	40	50	2300	5070	2.1	30	137	A6/30 kmph	A6 / 20 mph
16.9-30	TR-21	10	15	TT	429	16.9	1486	58.5	686	27	4369	172	40	50	2500	5500	2.1	30	140	A6/30 kmph	A6 / 20 mph
16.9-30	TR-21	12	15	TT	429	16.9	1486	58.5	686	27	4369	172	40	50	2725	5995	2.5	36	143	A6/30 kmph	A6 / 20 mph
16.9-30	TR-21	14	15	TT	429	16.9	1486	58.5	686	27	4369	172	40	50	3000	6600	2.7	40	146	A6/30 kmph	A6 / 20 mph
18.4-30	TR-21	8	16	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	42	52	2436	5359	1.4	20	139	A6/30 kmph	A6 / 20 mph
18.4-30	TR-21	10	16	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	42	52	2650	5830	1.9	27	142	A6/30 kmph	A6 / 20 mph
18.4-30	TR-21	12	16	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	42	52	2865	6303	2.3	33	144	A6/30 kmph	A6 / 20 mph
18.4-30	TR-21	14	16	TT	467	18.4	1544	60.8	711	28.0	4851	191.0	42	52	3250	7105	2.3	33	149	A6/30 kmph	A6 / 20 mph